


# Panel light

Our new LED panel lights are more accessible than ever before. The sleek and minimal construction allows for the easiest of installations. Now available in a 5-inch model.



RECESSED



**NEW**

Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>5003-CC</b>	3"	8 W	560 lm	640 lm	80	2700, 3000, 3500, 4000, 5000 K	120 V
<b>5004-CC</b>	4"	11 W	770 lm	880 lm			
<b>5005-CC</b>	5"	12 W	800 lm	980 lm			
<b>5006-CC</b>	6"	14 W	980 lm	1120 lm			

**Specifications**

Every fixture includes a junction box with an integrated driver  
 Over 35,000 hours of service life  
 Can be daisy chained  
 Smooth 360° wide spread  
 Minimal heat emission  
 Frosted lens  
 Edge lit technology  
 Cast aluminum construction  
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K  
 Easy-access CCT switch on panel wire  
 Very low profile  
 IC certification (suitable for direct contact with insulation)

Air-tight certified as per ASTM E283-04  
 Suitable for wet locations  
 Ideal operating temperature: -20° to 40° C  
 Refer to website for dimmer compatibility  
 5-year warranty

**Finish**

- **BK** Black (5004, 5005, 5006)
- **SN** Satin Nickel (5004)
- **WH** White (5003, 5004, 5005, 5006)

**Note**

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

**Accessories**

- REC-5CCT-EXT108**  
108" extension cable
- RFP-23 (5003)**  
Rough-in plate
- RFP-46 (5004, 5006)**  
Rough-in plate
- RFP-58 (5005)**  
Rough-in plate
- RFP-UNI (5003, 5004, 5006)**  
Universal rough-in plate

**Order example**

**5005-CC-WH**  
 White 5" round panel with 800 lumens at 3000 K



**5003-CC** Ø3 3/8" 



Ø3 3/4" x 0.5"

**5004-CC** Ø4 1/4" 




Ø4 3/4" x 0.5"

**5005-CC** Ø5 3/8" 



Ø5 7/8" x 0.5"

**5006-CC** Ø6 1/2" 



Ø7 1/8" x 0.5"